



MARQUE
FRANÇAISE

evolite



L

LAMPARA DESCARGA - INTEMPERIE -
ILUMINACIÓN LED - ACCESORIOS

EVOLITE

Tarifa 2022

www.soundlightspain.com

1. MOVING HEAD

2.1 SERIE LED

	EVO BEAM 60 -CR	Equipped with a 60W white 7500K LED. Control modes: DMX cable, automatic, automatic with sound detection. 2 DMX modes: 10 or 12 channels. Beam angle: 2°. Frost. 14-colour wheel + white / 17 gobo fixed wheel. 8 facets rotating prism. Luminous flux: 59728lx @ 2,5m Dim: 243 x 151 x 305mm / Weight: 4.38kg	379,50€
	EVO BEAM 100	Equipped with a 100W white LED. Control modes: DMX cable, automatic, automatic with sound detection. Beam angle: 4°. 11 color wheel + white 12 fixed Gobos, 8 facets circular rotating prism. 6 facets linear rotating prism. Luminous flux: 83000lx @ 3m Dim: 389 x 252 x 185mm / Weight: 6kg	712,83€
	EVO SPOT 60 -CR	Equipped with a 60W white 7500K LED. Control modes: DMX cable, automatic, automatic with sound detection. Beam angle: 14°. Motorized focus 8-colour wheel + white / 7 fixed gobos 3 faceted rotating prism. Luminous flow: 13072lx @ 2,5m Dim: 243 x 151 x 301mm / Weight: 4.78kg	422,50€
	EVO SPOT 120	Equipped with a 120W white 7500K LED. Control mode: DMX cable, W-DMX (Wireless Solution), automatic, sound detection. Wireless Solution receiver included. 2 DMX mode: 14 or 16 channels. Beam angle: 16°. 7 colors + white / 6 rotating gobos. 3 facets rotating prism. Luminous flow: 10450lx @ 2,5m Dim: 266 x 177 x 362mm / Weight: 8.6kg	749,00€
	EVO SPOT 180	Equipped with a 180W white 7500K LED. Control mode: DMX cable, W-DMX (Wireless Solution), automatic, sound detection. Wireless Solution receiver included 2 DMX mode: 14 or 16 channels. Beam angle: 16°. 7 colors + white / 6 glass rotating gobos / 11 fix metal gobos .3 facets rotating prism. Luminous flow: 27840lx @ 2,5m Dim: 307 x 224 x 418mm / Weight: 10.38kg	999,50€
	EVO SPOT 250 -Z	Equipped with a 250W white 7500K LED. Control mode: DMX cable, W-DMX (Wireless Solution), automatic, sound detection. Wireless Solution receiver included. Beam angle: from 12° to 36°. 7 colors + white / 6 rotating gobos + 8 fix gobos 3 facets rotating prism. Luminous flow: 31600lx @ 2,5m Dim: 357 x 224 x 505mm / Weight: 14kg	1.499,50€

1. MOVING HEAD



EVO WASH610 – CR Z

Equipped with 6 LED of 10W RGBW 4in1.CTB / CTO 2700K-8000K
Control modes:DMX cable,automatic,automatic with sound detection
2 DMX modes: 13 or 15 channels.Beam angle: 6°-60°. Motorized zoom
Luminous flux at 6': 45540lx @ 1m
Dim: 243 x 151 x 278mm / Weight: 3.88kg

399,50€



EVO WASH730 – Z PIX

Equipped with 7 LED of 30W RGBW 4 in 1.Control modes: DMX cable,
automatic, automatic with sound detection.Beam angle: 6°-60°.
Motorized zoom.Wireless Solution DMX receiver
Luminous flow @ 1m: 115000lx, Luminous flow @ 5m: 7230lx
Dim: 267 x 170 x 333mm / Weight: 6.5kg

756,50€



**EVO WASH740-Z
STREP**

Equipped with 7 LED of 40W RGBW 4 in 1Control modes: DMX
cables, W-DMX (Wireless Solution), automatic, sound detection
Equipped with a Wireless DMX Wireless Solution receiver Motorized
zoom. Beam angle: adjustable from 6°to 60°Luminous flux max @
1m: 153,441.Max luminous flux @ 5m: 9525
Dim: 380 x 200 x 400mm / Weight: 9.5kg

1.124,50€



DIAMOND 1915Z

DIAMOND 19X15Z- Wash LED moving head with zoom and flower
effect- Light source : 19x15W OSRAM- DMX operational mode : 21
- Wash LED moving head with zoom and flower effect- Light source :
19x15W OSRAM- DMX operational
mode : 21 - 23 - 35 - 78 - 92 - 97 channels- Pan : 540°/tilt:270°-
Strob effect with variable speed- Pixel control of each LED-
Dimmer(0-100%) with different. include flightcase

1.475,50€



DIAMOND PLUS

Equipped with 19 LED of 40W RGBW 4 in 1.Control modes: DMX
cables, automatic, sound detection.7 DMX modes:
21/23/35/78/92/97 or 99 channels.Motorized zoom. Beam angle:
adjustable from 3°to 45°.Luminous flux at 1m: 113,500 l
Dim: 376 x 418 x 372mm / Weight: 18kg / include flightcase

2.799,35€

EVO BEAM 60 -CR FC

Flightcase para modelo EVO BEam 60 (2 unidades)

194,80€

EVO BEAM 100 FC

Flightcase para modelo EVO BEam 100 (2 unidades)

214,50€

EVO SPOT 60 -CR FC

Flightcase para modelo EVO Spot 60 (2 unidades)

257,50€

EVO SPOT 120 FC

Flightcase para modelo EVO Spot 120(2 unidades)

301,15€

EVO SPOT 180 FC

Flightcase para modelo EVO Spot 180(2 unidades)

387,15€

EVO SPOT 250 -Z FC

Flightcase para modelo EVO Spot 250 (2 unidades)

400,85€

EVO WASH610-CRZ FC

Flightcase para modelo Air wash 610 CR Z (2 unidades)

195,85€

EVO WASH730-Z PIXFC

Flightcase para modelo Air wash 730 Z (2 unidades)

301,15€

**EVO WASH740-Z
STREP FC**

Flightcase para modelo Air wash 740 Z (2 unidades)

322,15€



evolite



1. MOVING HEAD

2.1 SERIE LAMPARA

	MOVING BEAM 1 R	Provided with 1R lamp/14 DMX channels/14 static gobos/13 colours + white/Prism rotation/DMX controlled operation or stand-alone operation with master/slave function/Sound-controlled via built-in microphone/Addressing via LCD control panel Dim: 330 x 230 x 430mm / Weight: 9.5kg	585,00€
	MOVING BEAM 2 R MKII	High output moving head beam effect/Light source: 2R lamp (included)/8 facets rotating prism/Colours wheel: 13 + white/Gobos wheel: 14 metal/Operational modes: master/slave, auto/sound, stand-alone and DMX-512 (15 or 19 channels) Dim: 430 x 250 x 330mm / Weight: 11.40kg	consultar
	MOVING BEAM 7 R	Osram 230W short arc lamp/Control modes: DMX cables, W-DMX (Wireless Solution), automatic, sound detection.2 DMX modes: 14 or 16 channels Motorized focus/Beam angle: 2,5°/11 colors, 16 fixed metal gobos/Prism 16 and 24 rotary facets/Frost filter/Luminous flow: 164230lx @ 10m/Dim: 307 x 224 x 435mm / Weight: 12.8kg	999,50€
	HYBRID 18 R	Philips lamp: 18R 350W included/13 fixed metal gobos wheel + 7 glass/11 colors + white/Effects wheel: water effect, and 3 effect gobos Frost/Prism 8 + 16 + 24 facets/Motorized zoom from 4,8° to 45°/Motorized focus/Dim: 400 x 300 x 650mm / Weight: 21kg	1840,50€
	MOVING BEAM 1 R FC	Flightcase para modelo BEAM 1 R (2 unidades)	292,50€
	MOVING BEAM 2 R MKII FC	Flightcase para modelo BEAM 2 R (2 unidades)	292,50€
	MOVING BEAM 7 R FC	Flightcase para modelo BEAM 7 R(2 unidades)	350,50€

3. LASER

3.1 SERIE M

	M 2000	Analog modulation sources/Red 638nm 500mW, green 520nm 500mW, blue 450nm 1000mW/Total power: 2000mW /Max projection angle: 40° 128 pre-recorded figures and animations / Galvo Scans 25 KPPS @ 8° ILDA interface in & out /Dim: 138 x 230 x 126mm / Weight: 3.2kg	725,83€
	M 3000	Analog modulation sources /Red 638nm 800mW, green 520nm 800mW, blue 450nm 1500mW /Total power: 3000mW /Max projection angle: 40° 128 pre-recorded figures and animations /Galvo Scans 25 KPPS @ 8° ILDA interface in & out /Dim: 138 x 230 x 126mm / Weight: 3.4kg	864,50€

3.2 SERIE INFINIUM

	INFINIUM 2200 RGB	Sources: Pure Diode with analog modulation /Red 638nm 600mW, green 520nm 600mW, blue 447nm 1000mW /Minimum power guaranteed after optics: 2086mW /Extremely weak divergence: <1,2mrad /Beam size: <4 x 2mm /Max projection angle: 60° /Very high speed Galvo Scans 35 KPPS @ 8°/ILDA interface in & out /Dim: 238 x 246 x 163mm / Weight: 8kg	1.471,17€
	INFINIUM 3300 RGB	Sources: Pure Diode with analog modulation /Red 638nm 900mW, green 520nm 800mW, blue 447nm 1600mW /Minimum guaranteed power after optics: 3040mW /Extremely weak divergence: <1,2mrad /Beam size: <4 x 2mm/Max projection angle: 60° /Galvo Scans 35 KPPS @ 8°/ILDA interface in & out/Dim: 238 x 246 x 163mm / Weight: 8kg	1.947,83€
	INFINIUM 6600 RGB	Sources: red 638nm 1700mW, green 520nm 1800mW, blue 445nm 3100mW/Total measured output power of optics: 6378mW Extremely weak divergence <1,2mrad /Beam size: <4 x 2mm Max projection angle: 60°/Analog modulation /Galvo Scans 35 KPPS @ 8°ILDA interface in & out /Dim: 270 x 278 x 190mm / Weight: 10.4kg (flight case included)	3.954,17€
	INFINIUM 10000 RGB	Sources: Pure diode analog /Red 638nm 2500mW/Green 520nm 2500mW Blue 445nm 5000mW /Extremely low divergence: <1,2mrad Beam size: <6 x 5mm /RGB modulation: 0 ~ 5V, analog <50kHz GT50 scan system 35 KPPS @ 8° /ILDA interface in & out Dim: 356 x 276 x 183mm / Weight: 14kg	12.025,00€
	INFINIUM 12000 RGB FB4	Integrated Pangolin FB4 interface /Sources: Pure Diode Red 638nm 3000mW, green 520nm 3000mW, blue 445nm 6000mW Total power: 12000mW /Extremely low divergence: <1,2mrad Beam size: <6 x 5mm / RGB modulation: 0 ~ 5V, analog <50kHz GT50 scan system 35 KPPS @ 8° /ILDA interface in & out Dim: 356 x 276 x 213mm / Weight: 14.7kg	16.228,35 €
	INFINIUM 25000 RGB FB4	Integrated Pangolin FB4 interface /Sources: red 638nm 7000mW, green 520nm 7000mW, blue 445nm 12000mW /Guaranteed power after optics: 25000mW /Extremely weak divergence: <1,2mrad /RGB modulation: 0 ~ 5V, analog <50kHz /GT50 scan system 35 KPPS @ 8° ILDA interface in & out /Dim: 488 x 308 x 245mm / Weight: 32kg	26.628,33€
	INFINIUM 5WRGB IP65	IP65 LASER Protection of diodes against electrostatic discharges by the LASORB system of Pangolin /Sources: red 1300mW 638nm, green 1500mW 520nm, blue 2200mW 455nm, Pure Diode /Total power: 5000mW /Extremely weak divergence: <1,1mrad /Beam size: <4 x 3mm. Max projection angle: 60° /Analog modulation 0 ~ 5V, <10kHz. Galvo Scans 35 KPPS @ 8° /Dim: 320 x 254 x 221mm / Weight: 11kg	5.308,35€

4. SERIE ARQUITECTURAL

	MX BAR 180	Ideal for wall washer /Controllable in DMX512: 3, 4, 5, 6, 9 channels.Variable speed strobe effect /Automatic effects: 5 types of color changes36 LED of 5W RGB /9 dimmer curves /Beam angle: 60° Dim: 480 x 104 x 147mm / Weight: 3.2kg	150,50€
---	-------------------	--	---------

4. SERIE ARQUITECTURAL (BATTERY)

	ArchiTECH 150 BAT	LED floodlight for indoor and outdoor lighting/Controllable by DMX512: 3, 5, 7 channels.7 control modes: wired DMX, wireless DMX, Auto, sound detection, Remote control supplied, manual, by ios / android Wifi application.Master-slave control, multi-unit for synchronous wireless control/Variable Speed Strobe Effect Dimensions: 231 x 170 x 236mm/ Net weight: 4.3kg	499,85€
	IP-BOX 6 X 15 W PACK	6 IP-BOX 6x15W RGBWA 5-in-1 LED floodlights Waterproof with IP65 protection 3 / 5 or 10 DMX channels 4 buttons and OLED display Auto, DMX512, master-slave, infrared remote control included, and wireless DMX modes Automatic Color, Fade, and Strobe modes Built-in wireless DMX transmitter/receiver Color temperature: 3000 - 7600K.	2990,00€
	IP-BOX 6 X 15 W	6 IP-BOX 6x15W RGBWA 5-in-1 LED floodlights Waterproof with IP65 protection 3 / 5 or 10 DMX channels 4 buttons and OLED display Auto, DMX512, master-slave, infrared remote control included, and wireless DMX modes Automatic Color, Fade, and Strobe modes Built-in wireless DMX transmitter/receiver Color temperature: 3000 - 7600K.	425,00€

4. SERIE ARQUITECTURAL IP-65 (OUTDOOR)

	Maxbar 210 IP65	LED bar for indoor and outdoor lighting Controllable by DMX512: 3, 4, 5, 6, 9 channels.Variable Speed Strobe Effect /Power supply on Trueone IN & OUT connector /Automatic effects: 5 kinds of color changes/42 5W RGB LED Dimensions: 535 x 153 x 182mm Net weight: 4kg	consultar
	PAR COB 150	150W architectural floodlight with RGBW colour mixing. LED : LED 150 W RGBW 4in1 - Power consumption : 150 W - DMX channels : 11 DMX channels - PMW rate : 900 Hz ~ 10 000 Hz - Dimming curve : 4 dimming curve modes - 6 DMX modes : 1CH,2CH,4CH,6CH,8CH,11CH - Control protocol : DMX512 - RDM	425,85€
	ArchiTECH 150	LED floodlight for indoor and outdoor lighting Controllable by DMX512: 3, 4, 5, 6, 9 channels.Variable Speed / Strobe Effect Dimmer (0-100%) with different curves /Automatic effects: 5 types of color changes /30 LED of 5W RGB /Dimensions: 231 x 170 x 236mm /Net weight: 3.84kg	290,00€
	archiTECH 270 IP65	54 LED of 5W RGB /Controllable in DMX512: 3, 4, 5, 6, 9 channels. Automatic effects: 5 types of color changes /9 dimmer curves Beam angle: 60°/Can be used outdoors (IP65) /Power supply on waterproof connector delivered /Dim: 360 x 221 x 266mm / Weight: 8.8kg	499,00€
	ArchiTECH 600	LED floodlight for indoor and outdoor lighting /Controllable by DMX512: 3, 6, 4, 8, 11 channels/Variable Speed Strobe Effect Reset option with factory presets.Automatic effects: 5 types of color changes/60 LEDs of 10W RGBW 4in1, 700mA Dimensions: 557.5 x 125 x 379.5mm /Net weight: 15.3kg	899,00€
	ArchiTECH 600 fc	Evolite - ARCHITECH600 FLIGHTCASE 2IN1 Flight case for Evolite ARCHITECH600, 2 spaces, especially designed for transporting and protecting your Evolite product.	425,00€
	PAR COB 150 fc	Evolite - PAR COB 150 FLIGHTCASE 8IN1 Flight case for Evolite PAR COB 150 FLIGHTCASE 8IN1	390,00€

5. SERIE HAZER


HazeBox 1500

Professional flightcase haze machine/Use with HAZER water-based fluid only /2 DMX channels /LCD screen for setting/ Heating time: 3 minutes /Heater power: 1500W /Continuous fog production Dim: 550 x 190 x 460mm / Weight: 16kg

552,50€

6. SERIE HEAVY FOG


HeavyFog 2000 C

Produces thick smoke that stays on the ground /Use with water and Evolite HeavyFog Fluid PRO)Power: 2000W /Controllable in DMX, manual, timer, with flow and fan control /HF remote control included (2 buttons)SUS304 stainless steel tank /Equipped with high quality ultrasonic nebulizers/ Dim: 610 x 380 x 470mm / Weight: 28kg

899,00€

HeavyFog 3000 C

Designed for very large performances /Use with water and Evolite HeavyFog Fluid Pro smoke fluid /Power: 3000W /Preheating time: 3 to 4 minutes /Controllable in DMX, manual, timer, HF remote control included with flow and fan control /Equipped with high quality ultrasonic nebulizers /Dim: 760 x 440 x 550mm / Weight: 42kg

1278,17€

HeavyFog 4000

Produces thick smoke that stays on the ground /Use with HeavyFog Fluid type heavy smoke liquid only /Heating body: 4000W /Use with water /Supplied with 2 black extendable tubes (1.5m) and diffusers /DMX control of fan speed and speed /Dimensions: 835 x 500 x 630mm /Gross weight: 53kg

1570,50€

3.1 SERIE PYROTECHNIC MACHINE


SPARK 600 TWIN SET

Set of 2 professional sparklers in flightcase- Easy and safe to use - For use with Evolite Evo Spark Powder only - 2 DMX channels - No special authorisation required - Heating time: 3 minutes - Tank capacity: 10-15 minutes - Heating element: 1500W - Self-cleaning function - Continuous spark production over 30 sec max: 1500W - Self-cleaning function - Continuous spark. production over 30 sec max - Max flow: 1 to 6 meters of projection - Radio

1514,0€


SPARK 600

EVO SPARK 600 - EVOLITE - Professional Spark Machine - Easy and safe to use - For use with Evolite Evo Spark Powder only - 2 DMX channels - No special authorisation required - Heating time: 3 minutes - Tank capacity: 10-15 minutes - Heating element: 1500W - Self-cleaning function - Continuous spark production over 30 sec max: 1500W - Self-cleaning function - Continuous spark. production over 30 sec max - Max flow: 1 to 6 meters of projection - Radio

735,50€

7. ACCESORIOS

	SPLITTER 4	DMX signal distributor with signal amplifier /1 input and 4 outputs All outputs are isolated from the input /Internal fuse: F-1A / 250V PTC /Supply voltage: AC 110-240V / 50-60Hz Dim: 200 x 200 x 70mm / Weight: 1.5kg	108,15€
	SPLITTER 8	DMX signal distributor with signal amplifier /1 input and 8 outputs All outputs are isolated from the input/Internal fuse: F-1A / 250V PTC Supply voltage: AC 110-240V / 50-60Hz Dim: 200 x 200 x 90mm / Weight: 2kg	157,45€
	DWT-512	2.4GHz wireless DMX transceiver /Range: 600 meters (without obstacle) /Wireless-Solution (W-DMX) and Wi-DMX compatible Power supply by 12V DC transformer /Dimensions: 129 x 114 x 34mm Net weight: 310g	129,50€
	EVOHAZERFLUIDPRO5L	5L Evolite Hazer Fluid high tech 5L liquid, complies CE	39,00€
	EVOHAZERFLUIDP20L	20L Evolite Hazer Fluid high tech 20L liquid, complies CE	105,00€
	EVOHEAVYFOGFLDPRO 5 L	Evolite Heavyfog Fluid PRO 5L heavy smoke liquid, produces a white smoke that dissipates once it leaves the ground, complies with NF and CE standards	24,90€
	EVOHEAVYFOGFLDPRO 20 L	Evolite Heavyfog Fluid PRO 20L heavy smoke liquid, produces a white smoke that dissipates once it leaves the ground, complies with NF and CE standards	89,45€
	SPARK 600 POWDER	EVO SPARK 600 POWDER - EVOLITE 200g bag - Titanium and zirconium alloy - Specially dedicated to the EVO SPARK 600	31,50€



CONDICIONES GENERALES DE VENTA

1. Los precios incluidos en esta lista corresponden a tarifa venta público, IVA no incluido. Todos los precios pueden variar sin previo aviso.
2. Los Clientes de SoundLight Spain deben acreditar, presentando la documentación que se les requiera, su actividad comercial o industrial antes de la aceptación de cualquier pedido. El establecimiento de relaciones comerciales con SoundLight Spain implica la aceptación de las condiciones de venta fijadas por la misma.
3. Las primeras operaciones con cada nuevo cliente se realizarán con pagos al contado (anticipado). Posteriormente, se asignará al cliente clasificación y riesgo financiero en función de la documentación aportada. De sobrepasarse el riesgo asignado, las ventas se realizarán con pagos al contado. Cualquier impago, supondrá la pérdida inmediata de condiciones de suministros de mercancía. El descuento por pronto pago es del 2%.
4. El plazo de entrega de nuestros productos es de 48/72 horas. Este plazo de entrega se encuentra sujeto a la disponibilidad de stock, y en algunas líneas de producto debe acordarse en el momento de realizar el pedido. Los pedidos de un importe superior a 1000€ serán enviados a portes pagados a través de la agencia que designe SoundLight Spain. Para el resto de los casos, los portes correrán a cargo del cliente y serán tramitados a través de la agencia que solicite el cliente.
5. En caso de que se produzca una incidencia en el transporte, será responsabilidad del cliente si el envío ha sido realizado a portes debidos, y de SoundLight Spain de ser a portes pagados. En envíos a portes pagados, la reclamación deberá realizarse en un plano inferior a 24h desde la recepción de la mercancía para que esta pueda ser atendida.
6. Todos los productos tienen una garantía de un año en componentes y mano de obra, siempre que el defecto no haya sido causado por un uso indebido del mismo o muestre evidencia de haber sido manipulado en un servicio técnico no autorizado.
7. La autorización de la garantía se realizará en el servicio técnico una vez recibido y analizado el producto. El cliente se hará cargo de los portes de ida, y de autorizarse la reparación en garantía estos se abonarán posteriormente. Los portes de vuelta serán a cargo de SoundLight Spain. Las reparaciones de productos deben realizarse siempre en los servicios técnicos oficiales. Los portes para reparaciones fuera de garantía correrán en su totalidad a cargo del cliente.
8. Solo se admitirán devoluciones de productos previa autorización expresa de SoundLight Spain.
9. Los precios publicados en esta lista corresponden a los productos descritos. El soporte técnico necesario para la realización de proyectos en los que se incluyen materiales se valorará y facturará como si fuera referencia física.

SAT OFICIAL S.L.S

Ctra de Mollet a Sabadell km 4,3 Nave I 2

Pol. Ind. Can Vinyals

08130 Santa Perpètua de Mogoda

comercial@soundlightspain.com



OFICINAS Y SHOWROOM

Tel. +34 93 544 86 91 / www.soundlightspain.com
Ctra. de Mollet a Sabadell Km 4,3 – Nave 12 / Pol. Ind.Can
Vinyals Santa Perpètua de Mogoda - Barcelona - 08130 España